



Konstruktion   Construction   Description		1/10" Getuftete Schlinge, strukturiert   1/10" Tufted loop pile, structured   1/10" Bouclé tufté, structuré
Polnutschicht   Pile material   Composition de la fibre		100% PA 6
Strapazierwert   Durability rating   Usage	EN 1307	intensiv 32   32 intensive   32 intensif
Komfortwert   Comfort class   Confort		Komfortklasse LC2   Luxury class LC2   Classe confort LC2
Stuhlrolleneignung   Castor chair use   Effet d'une chaise à roulette		intensive Nutzung   intensive use   utilisation intensive
Gesamtdicke   Total thickness   Epaisseur totale	EN 1307	≈ 5,8 mm
Gesamtgewicht   Total weight   Poids total	EN 1307	≈ 1.700 g/m <sup>2</sup>
Poleinsatzgewicht   Pile weight   Poids de velours	EN 1307	≈ 720 g/m <sup>2</sup>
Brandverhalten   Fire rating   Comportement au feu	DIN EN 13501-1	C <sub>fl</sub> -s1 ASTM E 648 + ASTM D2859
Trittschallschutz   Impact noise insulation   Isolation acoustique	DIN EN ISO 10140	26 dB
Schallabsorptionsgrad   Sound absorption   Absorption phonique	DIN EN ISO 354	α <sub>w</sub> 0,15

Broadloom



