



Konstruktion Construction Description	1/10" Getufteter Soft-Glanz-Saxony, uni 1/10" Tufted soft-gloss-saxony, plain 1/10" tufté Saxony doux brillant, uni
Polnutschicht Pile material Composition de la fibre	100 % PA 6.6
Strapazierwert Durability rating Usage	EN 1307 stark 23 heavy 23 fort 23
Komfortwert Comfort class Confort	Komfortklasse LC5 Luxury class LC5 Classe confort LC5
Stuhlrolleneignung Castor chair use Effet d'une chaise à roulette	gelegentliche Nutzung occasional use utilisation occasionnelle
Gesamtstärke Total thickness Epaisseur totale	EN 1307 Broadloom: ≈ 10,0 mm Plank: ≈ 12,5 mm
Gesamtgewicht Total weight Poids total	EN 1307 Broadloom: ≈ 2.295 g/m ² Plank: ≈ 2.500 g/m ²
Poleinsatzgewicht Pile weight Poids de velours	EN 1307 ≈ 1.380 g/m ²
Brandverhalten Fire rating Comportement au feu	DIN EN 13501-1 Broadloom: C _{fl} -s1 Plank: C _{fl} -s1
Trittschallschutz Impact noise insulation Isolation acoustique	DIN EN ISO 10140 Broadloom: 29 dB Plank: ≥ 25 dB
Schallabsorptionsgrad Sound absorption Absorption phonique	DIN EN ISO 354 Broadloom: α _w 0,25

Broadloom

Plank



