



1P82




1P83




2F87




3R99



3S00



4H58



51A0



7H31



7H32



9H01

Konstruktion Construction Description		1/10" Getufteter Schlinge, tuftgemustert 1/10" Tufted loop pile, tuft patterned 1/10" Bouclé tufté, tufté à dessin
Polnutschicht Pile material Composition de la fibre		100 % PA 6, ECONYL®
Strapazierwert Durability rating Usage	EN 1307	extrem 33 33 extreme 33 extrême
Komfortwert Comfort class Confort		Komfortklasse LC2 Luxury class LC2 Classe confort LC2
Stuhlleneignung Castor chair use Effet d'une chaise à roulette		intensive Nutzung intensive use utilisation intensive
Gesamtdicke Total thickness Epaisseur totale	EN 1307	≈ 6,0 mm
Gesamtgewicht Total weight Poids total	EN 1307	≈ 1.695 g/m ²
Poleinsatzgewicht Pile weight Poids de velours	EN 1307	≈ 675 g/m ²
Brandverhalten Fire rating Comportement au feu	DIN EN 13501-1	B _{fl} -s1 ASTM E 648 + ASTM D2859
Trittschallschutz Impact noise insulation Isolation acoustique	DIN EN ISO 10140	20 dB
Schallabsorptionsgrad Sound absorption Absorption phonique	DIN EN ISO 354	α _w 0,15

ECONYL®
Made with 100% Regenerated Nylon

Broadloom



